

Plastic Infrared Emitting Diode

OP265, OP266 Series (A, B, D, W)



Features:

- T-1 (3 mm) package style
- Choice of narrow or wide irradiance pattern
- Choice of dome or flat lens
- Mechanically and spectrally matched to other OPTEK devices
- Higher power output than GaAs at equivalent drive currents
- 890 nm diodes



Description:

Each device in the **OP265** and **OP266** series is a high intensity gallium aluminum arsenide infrared emitting diode (GaAlAs) that is molded in an IR transmissive clear epoxy package with either a dome or flat lens. Devices feature narrow and wide irradiance patterns and a variety of electrical characteristics. The small T-1 package style makes these devices ideal for space-limited applications.

OP265 devices conform to the OP505 and OP535 series devices. OP266 devices conform to OP506 series devices.

Please refer to Application Bulletins 208 and 210 for additional design information and reliability (degradation) data.

Applications:

- Space-limited applications
- Applications requiring coupling efficiency
- Battery-operated or voltage-limited applications

| Ordering Information | | | | | |
|----------------------|---------------------|---|----------------------------------|------------------|-------------|
| Part Number | LED Peak Wavelength | Output Power (mW/cm ²) Min / Max | I _F (mA) Typ / Max | Total Beam Angle | Lead Length |
| OP265A | 890 nm | 2.70 / NA | 20 / 50 | 18° | See page 2 |
| OP265B | | 1.65 / 4.70 | | | |
| OP265D | | 0.54 / NA | | | |
| OP265W | | 1.00 / NA | | | |
| OP266A | | 2.70 / NA | | 18° | |
| OP266B | | 1.65 / 4.70 | | | |
| OP266D | | 0.54 / NA | | | |
| OP266W | | 1.00 / NA | | | |



RoHS

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


TT Electronics | OPTEK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Plastic Infrared Emitting Diode


OP265, OP266 Series (A, B, D, W)



OP265 (A, B, D)




OP265W




DIMENSIONS ARE IN: [MILLIMETERS] INCHES

OP266 (A, B, D)



OP266W



| Pin # | LED |
|-------|---------|
| 1 | Cathode |
| 2 | Anode |

CONTAINS POLYSULFONE
To avoid stress cracking, we suggest using ND Industries' **Vibra-Tite** for thread-locking. **Vibra-Tite** evaporates fast without causing structural failure in OPTEK'S molded plastics.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Plastic Infrared Emitting Diode

OP265, OP266 Series (A, B, D, W)



Electrical Specifications

Absolute Maximum Ratings ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)


| | |
|---|-----------------------|
| Storage and Operating Temperature Range | -40 °C to +100 °C |
| Reverse Voltage | 2.0 V |
| Continuous Forward Current | 50 mA |
| Peak Forward Current (1 μs pulse width, 300 pps) | 3.0 A |
| Lead Soldering Temperature [1/16 inch (1.6 mm) from case for 5 seconds with soldering iron] | 260 °C |
| Power Dissipation | 100 mW ⁽¹⁾ |

Electrical Characteristics ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|----------------------------|---|----------------------|--------------------------|----------------|--------------------|--|
| Input Diode | | | | | | |
| $E_{E(APT)}$ | Apertured Radiant Incidence OP265A, OP266A OP265B, OP266B OP265D, OP266D | 2.70 1.65 0.54 | - - - | - 4.70 - | mW/cm ² | $I_F = 20\text{ mA}^{(2)}$ |
| P_O | Radiant Power Output OP265, OP266 (A, B, D) OP265W, OP266W | - 1.00 | - - | - - | mW | $I_F = 20\text{ mA}$ |
| V_F | Forward Voltage | - | - | 1.80 | V | $I_F = 20\text{ mA}$ |
| I_R | Reverse Current | - | - | 100 | μA | $V_R = 2\text{ V}$ |
| λ_P | Wavelength at Peak Emission | - | 890 | - | nm | $I_F = 10\text{ mA}$ |
| B | Spectral Bandwidth between Half Power Points | - | 80 | - | nm | $I_F = 10\text{ mA}$ |
| $\Delta\lambda_P/\Delta T$ | Spectral Shift with Temperature OP265, OP266 (A, B, D) OP265W, OP266W | - - | ± 0.30 ± 0.18 | - - | nm/°C | $I_F = \text{Constant}$ |
| θ_{HP} | Emission Angle at Half Power Points OP265, OP266 (A, B, D) OP265W, OP266W | - - | 18 90 | - - | Degree | $I_F = 20\text{ mA}$ |
| t_r | Output Rise Time | - | 500 | - | ns | $I_{F(PK)} = 100\text{ mA}$, PW=10 μs , D.C.=10.0% |
| t_f | Output Fall Time | - | 250 | - | ns | $I_{F(PK)} = 100\text{ mA}$, PW=10 μs , D.C.=10.0% |

Notes:

- Derate linearly 1.33 mW/°C above 25°C
- $E_{E(APT)}$ is a measurement of the average apertured radiant incidence upon a sensing area 0.081" (2.06 mm) in diameter, perpendicular to and centered on the mechanical axis of the lens, and 0.590" (14.99 mm) from the measurement surface. $E_{E(APT)}$ is not necessarily uniform within the measured areas.



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com





Plastic Infrared Emitting Diode

OP265, OP266 Series (A, B, D, W)



Performance

OP265, OP266 (A, B, D, W)



General Note
 TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
 1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com